

Hiresta-UX MCP-HT800

High Performance Resistivity Meter

Hiresta-UX

Measuring range $10^3 \sim 10^{14} \Omega$


Extended measuring range of $10^3 \sim 10^{14} \Omega$
Applicable for various types of materials



- Extensive measurement range of $10^3 \sim 10^{14} \Omega$
- 29 steps of voltage apply utilizing Auto Sweep Function
- Built-in Switch Box
- Compatible with all Hiresta UP probes

ASTM D257 Compatible

Standard Package



URS Probe
MCP-HTP14 (RMH214)



URS Probe checker
MCP-TRURS (RMH327)



Protection gloves
MCP-GV (RMJ803)

Hiresta-UX

(MCP-HT800)

For high accuracy measurements of both surface and volume resistivity in high resistivity range.

MCP Probe specially designed for measurement of various materials

- Single action to measure $[\Omega]$, $[\Omega/\square]$ and $[\Omega/\text{cm}]$
- Easy operation for RCF selection, measurement, data storage and data output

● By connecting to a unique measurement table "Resitable" (optional), volume resistivity can be measured.



Uses

Production Engineering ■ Quality Control ■ R&D

Applications

■ Antistatic materials, flooring materials, paper, packing materials, paint, fiber, concrete, ceramics, plastics, films, etc.

Features

- Measures conductive materials and anti-static materials at the extensive measuring range of $10^3 \sim 10^{14} \Omega$.
- 29 steps of applied voltage with Auto Sweep Function enables measuring voltage dependence of resistance value.
- With the new Built-in Switch Box, volume resistivity can be measured just by connecting a "Resitable" (optional) to Hiresta UX.
- Up to 2000 measurement results can be exported to USB memory stick.



● Stable measurement with Probe Fixer (optional)



● Validate probe functionality with Probe Checker



● Foot Switch (optional) enables remote start

Specifications

Method of Measurement	Constant-voltage Apply/Leak-current
Range Switching	Automatic, Manual
Display	640 × 480, 7.5 inch full-color TFT LCD touch panel
Comparator	Maximum and Minimum values can be set manually
Probe	MCP probe (URS, UR, UR-SS, UR-100, UA, J-Box X-Type)
Data Output	USB memory
Input Power	AC85 ~ 264V 47 ~ 63Hz
Dimensions & Weight	W330 × D270 × H113mm (Lid opened: W330 × D270 × H215mm) 2.4kg
Standard Package	URS Probe: RMH214 Probe checker: RMH327 Protection gloves: RMJ803

*Power cable not included.

Measurement Range and Trueness

1 ~ 10V	$10^3 \sim 10^9 [\Omega] : \pm 2\%$	$10^{10} [\Omega] : \pm 3\%$			
20 ~ 400V	$10^6 \sim 10^{10} [\Omega] : \pm 2\%$	$10^{11} [\Omega] : \pm 3\%$			
500 ~ 900V	$10^7 \sim 10^{10} [\Omega] : \pm 2\%$	$10^{11} [\Omega] : \pm 3\%$	$10^{12} [\Omega] : \pm 4\%$		
1000V	$10^8 \sim 10^{10} [\Omega] : \pm 2\%$	$10^{11} [\Omega] : \pm 3\%$	$10^{12} [\Omega] : \pm 4\%$	$10^{13} [\Omega] : \pm 5\%$	$10^{14} [\Omega] : \pm 12\%$


Options

Ring Probes



● Probe checkers are available for each probe (500M Ω)


2-Pin Probe



URS Probe Fixer



Compatible with JIS K 6911



*This product has a maximum voltage of 1,000V, take care to avoid electric shock.

MITSUBISHI CHEMICAL ANALYTECH CO., LTD.

370 Enzo, Chigasaki, Kanagawa 253-0084, Japan
Tel: +81-467-86-3864 Fax: +81-467-86-3862
URL: <http://www.mccat.co.jp>